

ISO CF4 LUB.

DESCRIPTION

ISO CF-4 LUB. is a high quality, universal motor oil of the latest generation engines . It can be used for all vehicles, as well gasoline and/or diesel engines & mixed fleets, manufactured from high quality mineral base oil & advanced technology additives to meet & exceed the most demanding lubrication requirements of modern turbo charged ultra high performance diesel (UHPD) & gasoline vehicles.

ADVANTAGES

- Strong oil film.
- High lubrication power.
- Low loss by evaporation.
- Effectively controls all kinds of rusting & corrosion.
- Very high resistance against oxidation.
- High detergent & dispersant properties.

SPECIFICATIONS

SAE	15W40 & 20W50
API	CF-4

PACKING

20 Litres & New Steel Drum & IBC

TYPICAL CHARACTERISTICS

Test	ASTM Method	Unit	Average results	
SAE-class	-	-	15W40	20W50
Density at 15°C	D1298	Kg/m ³	885	892
Viscosity at -20°C	D5293	cP	7000	9500
Viscosity at 40°C	D445	CSt	130	180
Viscosity at 100°C	D445	CSt	15.8	20.5
Viscosity index	D2270	-	129	131
Pour point	D97	°C	-27	-24
TBN	D2896	mgKOH/g	13	13
Flash point °C	D92	°C	236	244
Sulphated ash	D874	Mass%	1.5	1.5